Create the SafeToSQL command

To use the SafeToSQL utility, run the Command Prompt, and then type the appropriate command syntax for the conversion you need to execute. Use the following descriptions to choose the options you need.

Command syntax

Use the following syntax when converting a SQL Safe archive file:

```
SafeToSQL source_file_path [-backupfile file_name] [ -backupset #] [-password pwd] [-list]
```

Where the following option is mandatory:

source_file_path

Defined as the complete directory path and file name of the SQL Safe archive containing the backup set to convert to Microsoft SQL Server backup format.

Options

The SafeToSQL utility provides the following options:

-backupfile filename

Provides the names of additional files in multi-file archives. You must specify each file in a multi-file archive and provide the complete path to the file.

-backupset

Specifies the index (1-based) of the backup set in an archive containing multiple backup sets. *If you do not specify the backup set index*, the backup set defaults to 1, the index of the first backup set in the archive.

-password pwd

Specifies the password for decrypting an encrypted backup set. *If the backup set is encrypted,* provide the password you specified during backup.

-list

Prints out the complete contents of the archive specified by source_file_path.

Output file name format

SafeToSQL uses the following file naming convention for SQL Safe backup files it converts to Microsoft SQL Server backup files:

filename_#.bak

Where the file name components are as follows:

filename

Specifies the name of the source archive file.

#

Specifies the name of the backup set index.

SQL Safe is a high-performance backup and recovery solution for your SQL Servers. Learn more >>

IDERA Website	Products	Purchase	Support	Community	About Us	Resources	Legal