

SQLcompliance Agent Trace Directory window

This window allows you to change the location of the agent trace directory. The SQLcompliance Agent temporarily stores collected SQL Server events in the trace directory until the files can be sent to the Collection Server. To optimize performance, consider specifying a directory that is not located on the local disk drive that hosts the databases of the audited SQL Server instance.

If you specify a different directory path, ensure the SQLcompliance Agent Service account has read, write, and delete privileges on that folder. SQL Compliance Manager does not change the security settings on existing folders.

If you are auditing a virtual SQL Server, ensure the specified folder is located on a shared data disk for the selected virtual SQL Server. SQL CM applies this change to the active node in the cluster hosting the virtual SQL Server. SQLcompliance Agent properties are later replicated from the active node to the passive nodes.

To change the trace directory, type the path of the preferred trace directory location, and then click **OK**.

SQL Compliance Manager audits all activity on your server. [Learn more > >](#)

| | | | | | | | |
|-------------------------------|--------------------------|--------------------------|-------------------------|---------------------------|---------------------------|--------------------------|-----------------------|
| Idera Website | Products | Purchase | Support | Resources | Community | About Us | Legal |
|-------------------------------|--------------------------|--------------------------|-------------------------|---------------------------|---------------------------|--------------------------|-----------------------|