

Insight SQL Server group tables

- [PW_PWII_INSTANCE_ID](#)
- [PW_SQDG_DATABASE_GRP](#)
- [PW_SQSG_SERVER_GRP](#)
- [PW_SQIG_INSTANCE_GRP](#)
- [PW_SQLG_LOGIN_GRP](#)
- [PW_SQPG_PROGRAM_GRP](#)
- [PW_SQMG_MACHINE_NAME_GRP](#)

PW_PWII_INSTANCE_ID

Defines the instances in the Precise installation.

Column Name	Column Description
PWII_ID	ID of the instance. Columns of XXXX_PWII_INSTANCE_ID have values from the column.
PWII_INSTANCE_NAME	Name of the instance.
PWII_TECHNOLOGY	Two characters defining the technology of the instance (such as OR for Oracle and JE for J2EE).
PWII_SERVER	Name of the server on which the instance is installed.

PW_SQDG_DATABASE_GRP

The SQL Server database group table.

Column Name	Column Description
SQDG_SQDN_ID	The ID of the database.
SQDG_INGD_ID	The ID of the database group running the SQL Server statement.

PW_SQSG_SERVER_GRP

The SQL Server server group table.

Column Name	Column Description
SQSG_INCE_ID	The ID of the server.
SQSG_INGD_ID	The ID of the server group running the SQL Server statement.

PW_SQIG_INSTANCE_GRP

The SQL Server instance group table.

Column Name	Column Description
SQIG_INCE_ID	The ID of the instance.
SQIG_INGD_ID	The ID of the instance group running the SQL Server statement.

PW_SQLG_LOGIN_GRP

The SQL Server Login name group table.

Column Name	Column Description
SQLG_SQLN_ID	The login ID.
SQLG_INGD_ID	The ID of the login group running the SQL Server statement.

PW_SQPG_PROGRAM_GRP

The SQL Server program group table.

Column Name	Column Description
SQPG_SQPN_ID	The ID of the program.
SQPG_INGD_ID	The ID of the program group running the SQL Server statement.

PW_SQMG_MACHINE_NAME_GRP

The SQL Server client group table.

Column Name	Column Description
SQMG_SQMN_ID	The ID of the client.
SQMG_INGD_ID	The ID of the client group running the SQL Server statement.