

Insight Oracle groups tables

- [PW_PWII_INSTANCE_ID](#)
- [PW_ORSG_SERVER_GRP](#)
- [PW_ORIG_INSTANCE_GRP](#)
- [PW_ORUG_USER_GRP](#)
- [PW_ORPG_PROGRAM_GRP](#)
- [PW_ORMG_MACHINE_NAME_GRP](#)

PW_PWII_INSTANCE_ID

Defines the instances in the Precise installation.

Column Name	Column Description
PWII_ID	ID of the instance. Columns of XXXX_PWII_INSTANCE_ID have values from the column.
PWII_INSTANCE_NAME	Name of the instance.
PWII_TECHNOLOGY	Two characters defining the technology of the instance (such as OR for Oracle and JE for J2EE).
PWII_SERVER	Name of the server on which the instance is installed.

PW_ORSG_SERVER_GRP

The Oracle server group table.

Column Name	Column Description
ORSG_INCE_ID	The ID of the server.
ORSG_INGD_ID	The ID of the server group running the Oracle statement.

PW_ORIG_INSTANCE_GRP

The Oracle instance group table.

Column Name	Column Description
ORIG_INCE_ID	The ID of the instance.
ORIG_INGD_ID	The ID of the instance group running the Oracle statement.

PW_ORUG_USER_GRP

The Oracle user group table.

Column Name	Column Description
ORUG_ORUS_ID	The ID of the user.
ORUG_INGD_ID	The ID of the user group running the Oracle statement.

PW_ORPG_PROGRAM_GRP

The Oracle program group table.

Column Name	Column Description
ORPG_ORPR_ID	The ID of the program.
ORPG_INGD_ID	The ID of the Oracle program group.

PW_ORMG_MACHINE_NAME_GRP

The Oracle client machine group table.

Column Name	Column Description
ORMG_ORMC_ID	The ID of the client.
ORMG_INGD_ID	The ID of the client group running the Oracle statement.