Import Sensitive Columns from CSV window

The Import Sensitive Columns window allows you to import a list of sensitive columns from a .csv file to speed the process of configuring your sensitive column auditing. Note that the .csv file must have a row for each database you want to add for sensitive column auditing. The first row value must be the **database name**, the second value must be the **table name** followed by values for table's **column names**. If a row has only two values, first for database name and second for table name, all the columns will be selected for sensitive columns. A row with only one value is invalid and will be ignored. See the following examples:

```
Databasel, Tablel, Columnl, Column2 (Valid Row)
Database2, Table2 (Valid Row)
Database3 (Invalid Row)
```

You can access this window from the Instance Details view by selecting Import Sensitive Columns from the drop-down list available below the Audited Databases section.

File Edit View	Auditing Alerting Agent Tools Help
New • • • • • • • • • • • • • • • • • • •	Enable Auditing Disable Auditing
	Archive and Retention
	Collect Audit Data
	Permissions Check
	Check Repository Integrity
	Capture Audit Snapshot
	Audit Snapshot Preferences
	Login Filter Options
	Collection Server Status
	Configure Repository Databases
	Import Sensitive Columns from CSV

Importing Sensitive Columns from .CSV

To import a .csv file containing sensitive column search details:

- 1. Click Browse to search for and then select the .csv file you want to import.
- 2. Check the table columns you want to include as sensitive columns and uncheck those table columns you want to ignore.
- 3. Click OK to import the file.

S Import Sensitive Columns from CSV		?	×
CSV file must have a row for each database you want to add for sensitive coll has to be database name, second value has to be table name followed by vanames. If a row has only two values, first for database name and second for ta will be selected for sensitive columns. A row with only one value is invalid and examples below: Database1, Table1, Column1, Column2 (Valid Row) Database2, Table2 (Valid Row) Database3 (Invalid Row)	umn auditing. F lues for table's able name, all th will be ignored	irst row va column ne column . See	alue Is
CSV File:		Browse	
Please check the table columns you want to add to sensitive columns and ur to ignore. Hierarchy of database names, table names and column names to be columns access is given below.	icheck those w	hich you t	want
	оĸ	Cance	4

IDERA | Products | Purchase | Support | Community | Resources | About Us | Legal