

# InstantRestore CLI Commands

SQL Safe provides you with CLI commands to help you manually perform an instant restore to a database.

To perform InstantRestore operations use the following commands:

- SQLsafeCmd InstantRestore <db\_name> <backup\_archive> [options]
- SQLsafeCmd InstantRestore <db\_name> <point\_in\_time> [options]

Where:

Action	Description
<db_name>	Name of the database.
<backup_archive>	Path to the backup archive.
<point_in_time>	Date/Time {"MM/dd/yyyy hh:mm:ss"} to restore to.

## Common Options

The following options help you perform InstantRestore operations:

Options	Descriptions
-BackupSet <index>	<index> - the index of the backup set within the backup archive. (1-based).
-DisconnectUsers	Disconnects all users from the target database before the restore operation begins.
- EncryptedRestorePassword <pwd>	<pwd> - the encrypted password used to decrypt the backup.
-InstanceName <name>	<name> - SQL server instance name.  Note: it is not required if the instance is set as a default on the target server.

-Move <logical_filename> <target_filename>	<p>To move the database logical database file to the physical target file.</p> <p>&lt;logical_filename&gt; - the database logical database file.</p> <p>&lt;target_filename&gt; - the physical target file.</p> <p>Corresponds to the WITH MOVE option in the RESTORE DATABASE T/SQL command.</p>
-Password <pwd>	<pwd> - the non-encrypted password used to encrypt the backup.
-Server <hostname>	<p>&lt;hostname&gt; - the hostname of server hosting the SQL Server where the operation should be performed.</p> <p>Note: this option is required for accessing remote or clustered SQL Servers (where applicable).</p>
-Replace	Override database if exists.

## Security Options

Secure your InstantRestore operations with the following options:

Options	Description
-NoPrompt	Never prompt for credentials even if necessary.
-SecurityModel <model>	<p>The security model used to log into SQL Server.</p> <p>&lt;model&gt; - {Integrated, SQL}.</p> <p>Note: Integrated (Windows authentication) is the default.</p>
-SqlUsername <username>	<username> - the SQL Server username. (SQL SecurityModel).
-SqlPassword <pwd>	<pwd> - the SQL Server password. (SQL SecurityModel).
-EncryptedSqlPassword <pwd>	<pwd> - the encrypted SQL Server password generated by EncryptSqlPassword action. (SQL SecurityModel).
-WindowsUsername <domain\user>	<domain\user> - the Windows user that will be used to read/write the backup archive.
-WindowsPassword <pwd>	<pwd> - the password for the Windows user.

- EncryptedWindowsPa ssword <pwd>	<pwd> - the encrypted password for the Windows user generated by EncryptWindowsPassword action.
---	---

## Advanced Options

The following advanced options help you perform InstantRestore operations:

Options	Description
-ArgsFile <filename>	<p>The path to a file containing command-line arguments.</p> <p>&lt;filename&gt; - specifies the file that contains the command line arguments.</p>
-Diff <filename>	<p>The differential backup.</p> <p>&lt;filename&gt; - the file path to the differential backup.</p> <p>This can be followed by -BackupFile, -BackupSet, or -Password to set individual options for this backup set.</p>
-Log <filename>	<p>The log backup.</p> <p>&lt;filename&gt; the file path to the log backup.</p> <p>This can be followed by -BackupFile, -BackupSet, or -Password to set individual options for this backup set.</p>
-BackupFile <filename>	<p>Specifies additional backup archive files to be used for striping backups.</p> <p>&lt;filename&gt; - specifies the backup archive files.</p> <p>Note: use once for each additional stripe.</p>
-IncludeLogins	<p>For backup, includes the database logins in the backup file.</p> <p>For restore, creates the logins from the backup file on the destination server.</p>
-KeepReplication	<p>Preserves replication settings when restoring a published database to a server other than that on which it was created.</p>
-NoChecksum	<p>Disables the validation of any checksums by the restore operation.</p> <p>Note: for SQL 2005 and later only.</p>

-MailTo <email_address>	<p>&lt;email_address&gt; - an email address(es) to send the notification via SMTP.</p> <p>Note: multiple addresses may be separated by spaces, semicolons, or commas.</p>
-NoStatus	Prevents status messages from being cached or sent to the Repository.
-RecoveryMode <mode> [-UndoFile <filename>]	<p>Specifies the mode in which to leave the database after the operation is completed.</p> <p>&lt;mode&gt; - {NoRecovery, Standby}.</p> <p>Note: for Standby mode an undo file may be specified with the -UndoFile option.</p>
-StopAt <datetime>	<p>Specifies the database to be restored to the state it was in as of the specified date and time.</p> <p>&lt;datetime&gt; - {"mm/dd/yyyy hh:mm:ss"}.</p> <p>Note: for Log BackupType only.</p>
-StopAtMark <mark> [-After <datetime>]	<p>Specifies recovery to the specified &lt;mark&gt;, including the transaction that contains the &lt;mark&gt;.</p> <p>Note: for Log BackupType only.</p>
-StopBeforeMark <mark> [-After <datetime>]	<p>Specifies recovery to the specified &lt;mark&gt; but does not include the transaction that contains the &lt;mark&gt;.</p> <p>Note: for Log BackupType only.</p>
-After <datetime>	<p>Recovery stops at the first &lt;mark&gt; having the specified name exactly at or after &lt;datetime&gt;.</p> <p>Note: only valid with -StopAtMark/-StopBeforeMark options.</p> <p>For Log BackupType only.</p>
-Wait	<p>Wait for hydration to complete before returning result of operation.</p> <p>Note: by default, it is set to return result of bringing database online.</p>

For detailed descriptions and available options, see the CLI Help (SQLsafeCmd help InstantRestore).

SQL **Safe** is a high-performance backup and recovery solution for your SQL Servers. [Learn more](#) > >

<b>IDERA Website</b>	<b>Products</b>	<b>Purchase</b>	<b>Support</b>	<b>Community</b>	<b>About Us</b>	<b>Resources</b>	<b>Legal</b>
--------------------------	-----------------	-----------------	----------------	------------------	---------------------	------------------	--------------