Object Level Recovery CLI Commands

SQL Safe provides you with CLI commands to help you manually restore database objects.

To perform ObjectLevelRecovery operations use the following commands:

- SQLsafeCmd ObjectLevelRecovery <db_name> <backup_archive> [options]
- SQLsafeCmd ObjectLevelRecovery <db_name> <point_in_time> [options]

Where:

Action	Description
<db_name>	Name of the database.
<backup_archive>	Path to the backup archive.
<point_in_time>	Date/Time {"MM/dd/yyyy hh:mm:ss"} to restore to.

Common Options

The following options help you perform ObjectLevelRecovery operations:

Options	Descriptions
-Async	Performs Action in background. Returns command control as soon as possible.
-InstanceName <name>	<name> - SQL server instance name. Note: it is not required if the instance is set as a default on the target server.
-Server <hostname>	<hostname> - the hostname of server hosting the SQL Server where the operation should be performed. Note: this option is required for accessing remote or clustered SQL Servers (where applicable).
-BackupFile <filename>	Specifies additional backup archive files to be used for striping backups. <filename> - specifies the backup archive files. Note: use once for each additional stripe.
-BackupSet <index>	<index> - the index of the backup set within the backup archive. (1-based).

-RestoreAs <db_name>	<db_name> - a database new name. Note: the default is "<dbName>OLR" name.
-DatabaseFilesLocation <path>	<path> - specifies the database files location.
-TemporaryVdbLocation <location_path>	<location_path> - location where save VDB files.
-TemporaryVdbServerName <hostname>	<hostname> - host where create VDB for OLR Restore action.
-Password <pwd>	<pwd> - the non-encrypted password used to encrypt the backup.

Advanced Options

The following advanced options help you perform ObjectLevelRecovery operations:

Options	Description
-ArgsFile <filename>	The path to a file containing command-line arguments. <filename> - specifies the file that contains the command line arguments.
-KeepReplication	Preserves replication settings when restoring a published database to a server other than that on which it was created.
-IncludeLogins	For backup, includes the database logins in the backup file. For restore, creates the logins from the backup file on the destination server.
-DisconnectUsers	Disconnects all users from the target database before the restore operation begins.
-ContinueAfterError	Instructs SQL Server to continue the operation despite encountering errors such as invalid checksums. Note: SQL 2005 and later only.
-VerifyOnly	Perform Verify Only Action.
-MailTo <email_address>	<email_address> - an email address(es) to send the notification via SMTP. Note: multiple addresses may be separated by spaces, semicolons, or commas.

-Threads <number>	<number> - specifies the number of threads that should be used to distribute the backup process across multiple processors.

Options for Objects to Recovery

The following options are required to perform ObjectLevelRecovery operations:

Options	Description
-SchemaObjects <name1> [<name2> ...]	<name1> [<name2> ...] - the list of database schema objects. * (select all).
-UserDefinedTypeObjects <name1> [<name2> ...]	<name1> [<name2> ...] - the list of database user defined type objects. * (select all).
-XmlCollectionObjects <name1> [<name2> ...]	<name1> [<name2> ...] - the list of database xml collection objects. * (select all).
-TableObjects <name1> [<name2> ...]	<name1> [<name2> ...] - the list of database table objects. * (select all).
-FunctionObjects <name1> [<name2> ...]	<name1> [<name2> ...] - the list of database function objects. * (select all).
-ViewObjects <name1> [<name2> ...]	<name1> [<name2> ...] - the list of database view objects. * (select all).
-StoredProcedureObjects <name1> [<name2> ...]	<name1> [<name2> ...] - the list of database stored procedure objects. * (select all).
-ConstraintObjects <name1> [<name2> ...]	<name1> [<name2> ...] - the list of database constraint objects. * (select all).

Security Options

Secure your ObjectLevelRecovery operations with the following options:

Options	Description
-NoPrompt	Never prompt for credentials even if necessary.
-SecurityModel <model>	The security model used to log into SQL Server. <model> - {Integrated, SQL}. Note: Integrated (Windows authentication) is the default.
-SqlUsername <username>	<username> - the SQL Server username. (SQL SecurityModel).

-SqlPassword <pwd>	<pwd> - the SQL Server password. (SQL SecurityModel).
-EncryptedSqlPassword <pwd>	<pwd> - the encrypted SQL Server password generated by EncryptSqlPassword action. (SQLSecurityModel).
-WindowsUsername <domain\user>	<domain\user> - the Windows user that will be used to read/write the backup archive.
-WindowsPassword <pwd>	<pwd> - the password for the Windows user.
-EncryptedWindowsPassword <pwd>	<pwd> - the encrypted password for the Windows user generated by EncryptWindowsPassword action.

For detailed descriptions and available options, see the CLI Help (`SQLsafeCmd help ObjectLevelRecovery`).