

# xp\_cmdshell enabled

## REASON

The xp\_cmdshell extended stored procedure allows a Windows shell command to be executed from within a SQL Server connection. This command can be used for malicious purposes and is disabled by default in SQL Server.

## RESOLUTION

If the command is not being used, or if the use of the command can be eliminated, you can disable xp\_cmdshell with this command:

```
exec sp_configure 'show advanced options',1
reconfigure
exec sp_configure 'xp_cmdshell',0
reconfigure
```

If xp\_cmdshell must remain enabled in your environment, consider changing the proxy account used to execute the commands under in order to reduce risk using the `sp_xp_cmdshell_proxy_account` command. Full details of how to accomplish this are available at [this link](#).

Need more help? Search the [Idera Customer Support Portal](#).

|                               |                          |                          |                         |                           |                           |                          |                       |
|-------------------------------|--------------------------|--------------------------|-------------------------|---------------------------|---------------------------|--------------------------|-----------------------|
| <a href="#">Idera Website</a> | <a href="#">Products</a> | <a href="#">Purchase</a> | <a href="#">Support</a> | <a href="#">Resources</a> | <a href="#">Community</a> | <a href="#">About Us</a> | <a href="#">Legal</a> |
|-------------------------------|--------------------------|--------------------------|-------------------------|---------------------------|---------------------------|--------------------------|-----------------------|