Configuring your browser for Windows Authentication

In order to be able to use Windows Authentication to log into SQL Enterprise Job Manager, you have to configure your browser settings.

Internet Explorer 9,10,11

To configure these versions of **Internet Explorer**, follow these steps:

1. Go to **Internet Options.**

2. Click **Security.**

3. Click **Internet** and then **Custom Level.**



4. Go to Scripting/Active scripting and make sure **Enable** is selected.

5. Then go to User Authentication/Logon and make sure **Automatic logon with current user name and password** is selected.

6. Click **OK.**


Security Settings - Internet Zone
Settings
Disable
Enable
Websites in less privileged web content zone can navigate in
Disable
Enable
Prompt
Scripting
Active scripting
Disable
Enable
Prompt
Allow Programmatic clipboard access
Disable
Enable
Prompt
*Takes effect after you restart your computer
Reset custom settings
Reset to:
Medium-high (default)
Reset...
OK
Cancel


Security Settings - Internet Zone
Settings
Disable
Enable
Enable XSS filter
Disable
Enable
Scripting of Java applets
Disable
Enable
Prompt
User Authentication
Logon
Anonymous logon
Automatic logon only in Intranet zone
Automatic logon with current user name and password
Prompt for user name and password
*Takes effect after you restart your computer
Reset custom settings
Reset to:
Medium-high (default)
Reset...
OK
Cancel

7. Click **Local intranet** and then **Sites.**



8. Type the following site **http://sqlj01** and click **Add**.

9. Click **Close**.



10. Go to **Advanced** and make sure **Enable Integrated Windows Authentication** is selected.

11. Click **OK**.



12. Go to **Tools** in the menu bar, and select **Compatibility View Settings**.



13. In the **Compatibility View Settings** window make sure **Display intranet sites in Compatibility View** is selected.

14. Click **Close.**



Configuring Google Chrome and Mozilla Firefox

To configure **Google Chrome**, you can go to the following link: http://dev.chromium.org/developers/design-documents/http-authentication.

To configure **Mozilla Firefox**, view the following steps:

1. Open your Mozilla Firefox browser and type **about:config**.

2. Click **I´ll be careful, I promise!**.



3. Search and double click **network.negotiate-auth.delegation-uris.**



4. Type https://localhost:9291. Click **OK**.

5. Search **network.automatic-ntlm-auth.trusted-uris**, double-click it and type the same value as before: https://localhost:9291. Click **OK.**

6. Close all instances of the Firefox browser to make the changes effective. Launch the browser again and access the application.