

Replication

This interface shows the replication graph and relationship of all registered MySQL servers, as well as SLAVE STATUS and MASTER STATUS where it applies on hovering over each of the server block. The display gets updated after every one minute.

The servers are color-coded to represent the different states of the replication servers: green denotes stable, red disconnected servers and yellow not in sync. The yellow color is decided if any of the following variables return the below value:

```
'SLAVE IO RUNNING' = No
```

or

```
'SLAVE SQL RUNNING' = No
```

or

```
'SECONDS BEHIND MASTER' >= 450 Secs (this is the default global value for all the servers. A user can also set a value according to their MySQL environment)
```

From Monyog 8.1.0, the user can set the **Seconds Behind Master** threshold value for all the servers in SQL DM for MySQL by clicking the icon in the **Seconds Behind Master** column or in the dialog pop-up upon clicking the respective server in the table/topology.

There are two interfaces that the user can choose to see the information about the replication setup:

- **Table of Parameters:** This table contains the result set of SHOW [ALL] SLAVE STATUS for servers which have been marked as replication slaves in SQL DM for MySQL. The first time the number of columns in the table is condensed to only display 'Essential Parameters'. To get the detailed view, you can select the option 'All Parameters' from the drop-down menu in the header.

REPLICATION OVERVIEW

Table of Parameters

AUTO REFRESH
5 Second(s)

SHOW
Essential Parameters




SERVER	SLAVE IO STATE	MASTER HOST	SLAVE IO RUNNING	SLAVE SQL RUNNING	SECONDS BEHIND MASTER	LAST IO ERROR
Master File: mysql-bin.000005 Position: 120						
Slave-Ger File: mysql-bin.000003 Position: 120	Waiting for master to send event	127.0.0.1	Yes	Yes	0	
Slave-US File: mysql-bin.000003 Position: 120		127.0.0.1	No	No		

You can sort any column which removes the hierarchy listing of servers. To view slaves in the hierarchy, click the **SHOW HIERARCHY** link.

Also, if the I/O thread ('Slave_IO_Running') is not running, it dynamically brings out the Last IO Error column for a quick view on what went wrong with the Slave IO Thread. It works similarly for SQL thread ('Slave_SQL_Running') as well.

REPLICATION OVERVIEW									
Table of Parameters		AUTO REFRESH 5 Second(s)		SHOW All Parameters		SHOW HIERARCHY			
SERVER	SLAVE IO STATE	MASTER HOST	MASTER USER	MASTER PORT	CONNECT RETRY	MASTER LOG FILE	READ MASTER LOG POS	RELAY LOG FILE	RELAY LOG POS
● Slave-Ger File: mysql-bin.000003 Position: 120	Waiting for master to send event	127.0.0.1	rsandbox	23700	60	mysql-bin.000005	120	mysql-relay.000012	283
▲ Slave-US File: mysql-bin.000003 Position: 120		127.0.0.1	rsandbox	23700	60	mysql-bin.000005	120	mysql-relay.000012	283
● Master File: mysql-bin.000005 Position: 120									

- Topology Chart:** This interface shows the replication graph and relationship of all registered MySQL servers which are marked as master/slave, as well as SLAVE STATUS and MASTER STATUS while hovering over each of the server blocks. The display gets updated at the user-specified refresh interval which is a browser-specific setting. The default interval is 5 seconds.



The server blocks on clicking gives the result set of SHOW [ALL] SLAVE STATUS for the slave and SHOW MASTER STATUS for the master servers.