

Detailed action items for removing tiers

This section contains the following topics

- [Action Items for removing tiers](#)
- [Detailed action items for J2EE](#)
- [Detailed action items for Oracle](#)
- [Detailed action items for Siebel](#)

Action Items for removing tiers

Some Tiers require action items to complete the un-installing or removal of the Tier. Usually, the action items are listed online, but some Tiers have detailed action items that are fully documented below.

Detailed action items for J2EE

Before you remove J2EE Tier Collectors, you should remove the Precise for J2EE configuration that was added when you performed post-installation tasks. To remove the configuration, shutdown the JVM, remove the configuration from the startup script, and then restart the JVM.

For more information, see [J2EE Post installation action items](#).



If you want to retain the instance or Tier history data, verify that the PMDB Maintenance (Weekly) process parameter is cleared. You are then able to view the data by installing a new instance using the same ID of the instance you deleted. For more information on the procedure for reusing an instance ID, see the Installing an uninstalled, old instance_id parameter section in the [Precise CLI Utility Reference Guide](#).

Detailed action items for Oracle

After removing the Oracle Tier Collectors, you need to perform the following task.

To completely remove the Oracle Tier Collectors

1. Log in to the server where the Precise for Oracle FocalPoint service is running as the Precise user.
2. Open a command line window and go to Precise installation folder.
3. Run the following command to drop the Precise for Oracle schema:

- **Windows**
`products\oracle\install\uninstall_schema.bat \`
`-h host -s sid -u`
`oracle-user -p password \`
`-t oracle-port -v oracle-version \`
`-i i3 installation directory`
- **UNIX**
`./products/oracle/install/uninstall_schema.sh \`
`-h host -s sid -u oracle-user -p password \`
`-t oracle-port -v oracle-version`
where `oracle-version` is 81, 90, or 100.

The uninstall script does not stop the Collector. It also does not drop the Precise Oracle user and its tablespaces. You may drop them using SQL*Plus.

4. Remove the following folder:
 - **Windows.** `products\oracle\fp\host\sid`
 - **UNIX.** `./products/oracle/fp/host/sid`

To drop the Precise Oracle user and its tablespaces

1. Log in to the server machine where the Oracle Tier Collector is running as the Precise user.
2. Open a command line window and go to the Precise installation folder.
3. Run the following command to stop the Oracle Tier Collector:
 - **Windows.** `products\oracle\install\uninstall_sys_obj.sql`
 - **UNIX.** `./products/oracle/install/uninstall_prod.sh sid`
4. If no other Oracle Tier Collectors are installed on this instance, it is recommended to connect as system administrator and perform the following tasks:
 - a. Edit the `uninstall_sys_obj.sql` file and replace the parameters according to the instructions in the file.
 - b. Save the `uninstall_sys_obj.sql` file.
 - c. Run the SQL script using SQL*Plus:
 - **Windows.** `products\oracle\install\uninstall_sys_obj.sql`
 - **UNIX.** `./products/oracle/install/uninstall_sys_obj.sql`

Detailed action items for Siebel

When the Siebel Tier Collectors have been removed, you can delete the Precise Interpoint Project from the Siebel Repository File (SRF). These tasks differ slightly depending on whether Interpoint is installed for a SQL Server or an Oracle database. See [Deleting the Precise Interpoint project from the SRF \(Oracle\)](#) and [Deleting the Precise Interpoint project from the SRF \(SQL Server\)](#).

Deleting the Precise Interpoint project from the SRF (Oracle)

Deleting this project from the SRF involves the following tasks:

- Removing changes in the Application_PreNavigate() function
- Removing the business object
- Removing the CX_VTS_SBL table
- Removing the Precise project

To remove changes in the Application_PreNavigate() function

1. In Siebel Tools, go to View > Options.
2. In the Development Tools Options dialog box, on the Object Explorer tab, select the Application Server Script check box to display this application on the Types tab in the Object Explorer.
3. In the Object Explorer, on the Types tab, select Application > Application Server Script.
4. In the Application Server Scripts panel, select the script called Application_PreNavigate.
5. From the Edit menu, choose **Delete Record**.

If you want to make additional changes to your application, you first need to close and then reopen Siebel Tools.

To remove the business object

1. In Siebel Tools, in the Object Explorer, on the Types tab, select **Business Object**.
2. In the Business Object panel, select the Business Object called VERITAS_SBL.
3. On the Types tab, select Business Object > Business Object Component.
4. In the Business Object Component panel, right-click the component called VERITAS_SBL and select **Delete Record**.

To remove the CX_VTS_SBL table

1. In Siebel Tools, in the Object Explorer, on the Types tab, select **Table**.
2. In the Table panel, right-click the table called CX_VTS_SBL. and select **Delete Record**.
3. Log in to the Siebel database with the Siebel user.
4. Run the following command:
`select * from user_views where view_name = 'CX_VTS_SBL';`
5. If a row is returned, run the following command:
`drop view CX_VTS_SBL;`
6. Run the following command:
`select * from user_tables where table_name = 'CX_VTS_SBL_TAB';`
7. If a row is returned, run the following command:
`drop table CX_VTS_SBL_TAB;`

To remove the Precise Interpoint project

1. In Siebel Tools, in the Object Explorer, on the Types tab, select **Project**.
2. In the Projects panel, search for the Precise Interpoint project.
3. Make the project inactive.

Deleting the Precise Interpoint project from the SRF (SQL Server)

Deleting this project from the SRF involves the following tasks:

- Removing changes in the Application_PreNavigate() function
- Removing the business object
- Removing the CX_VTSSPID table
- Removing the Precise project

To remove changes in the Application_PreNavigate() function

1. In Siebel Tools, go to View > Options.
2. In the Development Tools Options dialog box, on the Object Explorer tab, select the Application Server Script check box to display this application on the Types tab in the Object Explorer.
3. In the Object Explorer, on the Types tab, select Application > Application Server Script.
4. In the Application Server Scripts panel, select the script called Application_PreNavigate.
5. On the Edit menu, choose **Delete Record**.

If you want to make additional changes to your application, you first need to close and then reopen Siebel Tools.

To remove the business object

1. In Siebel Tools, in the Object Explorer, on the Types tab, select **Business Object**.
2. In the Business Object panel, select the Business Object called VTS_SPID.
3. On the Types tab, select Business Object > Business Object Component. The Business Object Component panel for the VTS_SPID Business Object opens.

4. In the Business Object Component panel, right-click the component called VTS_SPID and select **Delete Record**.

To remove the CX_VTSSPID table

1. In Siebel Tools, in the Object Explorer, on the Types tab, select **Table**.
2. In the Table panel, right-click the table called CX_VTSSPID and select **Delete Record**.
3. Log in to the Siebel database with the Siebel user.
4. Run the following command:

```
select * from user_views where view_name = 'CX_VTSSPID';
```
5. If a row is returned, run the following command:

```
drop view CX_VTSSPID;
```
6. Run the following command:

```
select * from user_tables where table_name = 'CX_VTSSPID_TAB';
```
7. If a row is returned, run the following command:

```
drop table CX_VTSSPID_TAB;
```

To remove the Precise Interpoint project

1. In Siebel Tools, in the Object Explorer, on the Types tab, select **Project**.
2. In the Projects panel, search for the Precise Interpoint project.
3. Make the project inactive.