

# Post-installation tasks for the Tuxedo tier collector

When the Tuxedo Tier Collectors have been installed, post-installation tasks may be required.

- Run the following commands only if they have not been previously run for other Tuxedo instances on this server and this server is a UNIX server:  
Log in as root user and run the following commands:  

```
cd <precise_root>/products/insight/install  
./tuxedo_root.sh
```
- A Tuxedo information system can have one or more Tuxedo servers. On each Tuxedo server, you can have one or more Tuxedo domains. A Tuxedo domain has a logical definition: it is an instance holding common business units and handling client processes. The Tuxedo Tier should be installed for each Tuxedo domain. Therefore, if your Tuxedo information system has more than one domain, you should create a Tuxedo Tier instance for each domain.



It is recommended to install the Insight Savvy for Tuxedo in each Tuxedo domain. To find out how many Tuxedo domains are running on your Tuxedo server machine, count how many BBL processes are running on this machine. On Windows, look for BBL processes in the Windows Task Manager. On UNIX, run the following command: `ps -ef | grep BBL`

To perform Tuxedo Tier post-installation tasks

1. In the Tuxedo Tier - Installation dialog box, click **Next**.
2. In the Tuxedo Tier - Post-Installation dialog box, follow the instructions to perform all post-installation tasks.
3. Click **Finish**.