

Post-installation tasks for WebSphere MQ tier collectors

Once the WebSphere MQ Tier Collectors have been installed, the following post-installation task may be required:

Setting the Queue Manager attributes

To set Queue Manager attributes on Windows

1. Go to **Start>Programs>IBM WebSphere MQ** and open the MQ Services utility.
2. Right-click the specific queue manager and select **Properties**.
3. On the Exits tab, click **Add**.
4. Set the attributes as follows:
 - **Name:** VeritasI3Agent
 - **Function:** PSI_EntryPoint
 - **Module:** <precise_root>\products\insight\bin\psi_mq_exits.dll
 - **[V] Data:** %ID%
 - **Sequence:** 100where %ID% is a hexadecimal number, such as 0x 920D212F.
5. Stop and restart the queue manager.

To set Queue Manager attributes on UNIX

1. Log in as the mqm user.
2. Copy all psi_mq_exits* files from the <precise_root>/products/insight/bin/ folder to the mq lib folder.
3. Open the qm.ini file of the relevant queue manager, located in the mq home/qmgrs folder, and add the following lines:

```
ApiExitLocal:
Sequence=100
Function=PSI_EntryPoint
Module=mq lib/psi_mq_
exitsName=VeritasI3Agent
Data=%KEY%
```

where %KEY% is a hexadecimal number, such as 0x920D212F.
4. Run the following command to stop the queue manager:

```
endmqm queue manager name
```
5. Run the following command to restart the queue manager:

```
strmqm queue manager name
```