

Insight general tables

- [PW_PWII_INSTANCE_ID](#)
- [PS_INGD_GROUPS_DEFS](#)
- [PS_INLD_LOCATION_DEFS](#)
- [PS_ISPD_PROC_AVAIL_DEFS](#)
- [PS_ISPR_PROC_AVAIL_RULES](#)
- [PS_ISPC_PROC_AVAIL_CONN](#)

PW_PWII_INSTANCE_ID

Defines the instances in the Precise installation.

Column Name	Column Description
PWII_ID	The instance ID. Columns of XXXX_PWII_INSTANCE_ID have values from the column.
PWII_INSTANCE_NAME	Name of the instance.
PWII_TECHNOLOGY	Two characters defining the technology of the instance (such as OR for Oracle and JEJE for J2EE).
PWII_SERVER	Name of the server on which the instance is installed.

PS_INGD_GROUPS_DEFS

A translation of all Insight grouped entities, excluding locations.

Column Name	Column Description
INGD_ID	The group ID.
INGD_NAME	The group name according to the joined entity, such as (Users (Grouped)).

PS_INLD_LOCATION_DEFS

A translation of all Insight client IPS groups to Locations.

Column Name	Column Description
INLD_ID	The group ID.
INLD_NAME	The locations.

PS_ISPD_PROC_AVAIL_DEFS

This table contains Alerts Process Availability (PA) Definitions.

Column Name	Column Description
ISPD_ID	PA definition ID.
ISPD_NAME	PA definition name.
ISPD_INTE_CODE	Technology code of the PA definition.

PS_ISPR_PROC_AVAIL_RULES

This table contains process names that comprise the Process Availability Definition.

Column Name	Column Description
ISPR_ISPD_ID	PA definition ID.
ISPR_USER_NAME	OS user name.

ISPR_RULE	Process name or text pattern.
-----------	-------------------------------

PS_ISPC_PROC_AVAIL_CONN

This table contains the association of Process Availability Definitions to Precise instances.

Column Name	Column Description
ISPC_ISPD_ID	PA definition ID.
ISPC_INTE_CODE	Technology code of the PA definition.
ISPC_TECH_DEFAULT	<i>Boolean.</i> Does this definition apply to all instances of the technology? (YES or NO)
ISPC_INCE_ID	Instance ID associated with the PA definition, if this definition is not the technology default.