

Log Shipping Backup CLI Commands

SQL Safe provides you with CLI commands to help you manually perform a log shipping primary backup.

To perform LogShipBackup operations use the following command:

- SQLsafeCmd LogShipBackup [options]

Where the required [options] are:

Options	Descriptions
-BackupLocation <path>	<path> - the network path where backups will be stored.
-DatabaseName <name>	<name> - name of the primary database.

Common Options

The following options help you perform LogShipBackup operations:

Options	Descriptions
-BckDstType <type>	The backup destination type is used for the backup. <type> - {0, 1, 2, 3, 4}.
- CompressionLevel <level>	The compression level used for the backup. <level> - {ispeed, isize, 0, 1, 2, 3, 4}. Note: if the compression level is not specified, ispeed is the default.
-EncryptionType <type>	The type of encryption used to encrypt the backup. <type> - {AES128, AES256}.
- EncryptedBackupPassword <pwd>	<pwd> - the encrypted password used to encrypt the backup. (Used with EncryptionType).

-Delete <n><time_period>	After a backup successfully completes, delete archives that are older than the specified amount of time. <n> - amount of time. <time_period> - {minutes, hours, days, weeks, months}. There must be NO SPACE between <n> and <time_period>. E.g., -delete 2hours. Note: if you use the space between <n> and <time_period>, the backup archive filename will be automatically generated with the following pattern: <instancename>_<databasename>_<backuptype>_<timestamp>.safe where the <timestamp> is in UTC time and in the form of YYYYMMDDHHMM.
-InstanceName <name>	<name> - SQL server instance name. Note: it is not required if the instance is set as a default on the target server.

Security Options

Secure your LogShipBackup operations with the following options:

Options	Description
-NoPrompt	Never prompt for credentials even if necessary.
-SecurityModel <model>	The security model used to log into SQL Server. <model> - {Integrated, SQL}. Note: Integrated (Windows authentication) is the default.
-SqlUsername <username>	<username> - the SQL Server username. (SQL SecurityModel).
-SqlPassword <pwd>	<pwd> - the SQL Server password. (SQL SecurityModel).
- EncryptedSqlPassword <pwd>	<pwd> - the encrypted SQL Server password generated by EncryptSqlPassword action. (SQLSecurityModel).
-WindowsUsername <domain\user>	<domain\user> - the Windows user that will be used to read/write the backup archive.

-WindowsPassword <pwd>	<pwd> - the password for the Windows user.
- EncryptedWindowsPa ssword <pwd>	<pwd> - the encrypted password for the Windows user generated by EncryptWindowsPassword action.

Advanced Options

The following advanced options help you perform LogShipBackup operations:

Options	Description
-MailTo <email_address>	<email_address> - an email address(es) to send the notification via SMTP. Note: multiple addresses may be separated by spaces, semicolons, or commas.
-Threads <number>	<number> - specifies the number of threads that should be used to distribute the backup process across multiple processors.
-RetryWrites <interval> <retry_time> <total_time>	On a network file error, retry every <interval> seconds for up to <retry_time> seconds. Total retry time allowed is <total_time> minutes.
-PreCommandRun	Specifies that a pre-command is expected. No value is expected here, just the presence of the parameter -PreCommandRun. Note: Optional.
- PreBackupDestination	The UNC location and filename of the pre-backup command. -PreBackupDestination = '\\myserver\safecommands\prebackupcommand.bat' Note: Optional.
-QuitJobPreJobFail	Quits the backup operation if the pre-backup command fails. No value is expected here, just the presence of the parameter -QuitJobPreJobFail. Note: Optional.
-PostCommandRun	Specifies that a post-command is expected. No value is expected here, just the presence of the parameter -PostCommandRun. Note: Optional.

- PostBackupDestination	The UNC location and filename of the post-backup command. -PostBackupDestination = '\\myserver\safecommands\postbackupcommand.bat' Note: Optional.
------------------------------------	---

For detailed descriptions and available options, see the CLI Help (SQLsafeCmd help LogShipBackup).

[IDERA](#) | [Products](#) | [Purchase](#) | [Support](#) | [Community](#) | [Resources](#) | [About Us](#) | [Legal](#)