

Add Database CLI Commands

SQL Safe provides you with CLI commands to help you manually add databases.

To add databases use the following commands:

- `SQLsafeCmd AddDatabase <policy_name> <db_name>`
- `SQLsafeCmd AddDatabase <policy_guid> <db_name>`
- `SQLsafeCmd AddDatabase <policy_name> <instance_name> <db_name> [primary|secondary]`
- `SQLsafeCmd AddDatabase <policy_guid> <instance_name> <db_name> [primary|secondary]`

Where:

Action	Description
<policy_name>	Name of the policy.
<policy_guid>	GUID of the policy.
<db_name>	Name of the database.
<instance_name>	Specifies the instance name. {server, instance}. Note: this parameter is optional for Backup policy and required for LogShipping policy.
[primary secondary]	Specifies the location. Note: the default value is "secondary" database. this parameter is optional for LogShipping policy.

For detailed descriptions and available options, see the CLI Help (`SQLsafeCmd help AddDatabase`).

SQL **Safe** is a high-performance backup and recovery solution for your SQL Servers. [Learn more >>](#)

IDERA Website	Products	Purchase	Support	Community	About Us	Resources	Legal
-------------------------------	--------------------------	--------------------------	-------------------------	---------------------------	--------------------------	---------------------------	-----------------------